

Balance 2500 EC



Quick Look

Cellular	Ethernet WAN	Ethernet LAN	Stateful Firewall Throughput	SpeedFusion VPN Throughput (No Encryption)	SpeedFusion VPN Throughput (256-bit AES)
No	0-16 (GE)*	0-16 (GE)*	30Gbps	4Gbps	4Gbps

Interfaces

SFP LAN/WAN	4 (10G SFP+) *
Wi-Fi AP	No
USB	1

Performance

Recommended Users	10000-20000+
Number of SpeedFusion VPN Peers	4000
Maximum Number of AP Supported	1500

Performance

SpeedFusion Hot Failover	Yes	High Availability	Yes
SpeedFusion WAN Smoothing	Yes	Content Filtering (Lite/Full)	Full
SpeedFusion Bandwidth Bonding	Yes	Pepwave AP Series Management	Yes
Remote SIM (used in SIM Injector)	No	Remote AP & Multiple Config Profiles Management	Yes
Central Management	InControl 2	LAN Bypass	Yes
Drop In Mode	Yes	Remote User Access	Yes

Core Funtionality

802.1q VLANs Supported	1024
Port-Based VLAN	Yes
Load Balancing & Failover	Yes
Load Balancing Algorithms	8
Inbound Load Balancing	Yes
InControl Cloud Management	Yes

IPsec/L2TP/PPTP VPN Functionality

SpeedFusion VPN	Yes
IPsec VPN (Network-to-Network)	Yes
Number of IPsec Tunnels	150
L2TP VPN Server	Yes
OpenVPN Server	Yes
PPTP VPN Server	Yes
Maximum PPTP/L2TP/ OpenVPN Users	1000
GRE (Network-to-Network)	5

Advanced QoS Functionality

Bandwidth Usage Monitor	Yes
QoS for VoIP and E-Commerce	Yes
User Groups Bandwidth Control	Yes
Web Blocking	Yes

Hardware

LACP (802.3ad) NIC Bonding	Yes
PoE+ Output	No
Rack-mount	Yes (1U)
Dual Hot Swap Power Supply	Yes
Power Consumption	65W (nominal) 150W (max.)
Operating Temperature	32° – 104°F 0° – 40°C

Certifications

FCC, CE, RoHS	Yes
Warranty	1-Year Limited Warranty

*SFP and Ethernet ports can be configured as WAN/LAN

[1] For a list of supported modems, please refer to <https://www.peplink.com/technology/4g3g-modem-support/>.

[2] Recommendation for sizing purposes only. No software restrictions applied.

[3] Router Throughput and SpeedFusion VPN Throughput is based on Ethernet frame sizes of 1280 or 1518 bytes. Actual performance can vary across different networking environments. Figures apply to the latest hardware revision. The throughput result is tested with DHCP/Static IP.

[4] The number of peer Peplink or Pepwave devices you can connect using SpeedFusion VPN.

[5] IPsec only supports connection with Cisco, Juniper, Peplink or Pepwave devices.

Balance 20/30 LTE/One/210/310 comes with AP Controller Standard, which supports up to two configuration profiles with multiple SSIDs, meaning that all APs will share the same configuration, and you can only manage APs on the local physical LAN. 305/310 5G/310 5G Fiber/380/380X/580/580X/710/1350/2500/SDX/SDX