


H3C Aolynk ES100 - 10G-HP PoE Full Gigabit Switch

Product Overview

H3C Aolynk ES100-10G-HP is a compact full-gigabit unmanaged PoE (Power over Ethernet) Ethernet switch launched by H3C Technology Co., Ltd. It adopts a metal shell design and meets green energy-saving and environmental protection standards. The product features Plug-and-Play capability, supports one-click switching of multiple business modes, and is suitable for typical application scenarios such as small and micro enterprises, retail chains, hotels, and campuses.



ES100-10G-HP

Product Features

High-Reliability Network Architecture

- Complies with IEEE802.3, IEEE802.3u, IEEE802.3x, and IEEE802.3ab Ethernet standards.
- Supports 6kV professional lightning protection for enhanced port protection.
- Supports PoE Watchdog: intelligently monitors abnormalities and automatically restarts; fault self-diagnosis reduces operation and maintenance costs.
- Supports long-distance PoE power supply (up to 250 meters), effectively controlling deployment costs and ensuring power supply stability.
- Supports upstream and downstream port isolation to improve network security and stability.
- Full-gigabit adaptive ports (10/100/1000Base-T) support Auto-Negotiation.
- Adopts a shared cache architecture to expand the cache space available for each port, effectively improving forwarding performance in scenarios with bursty large traffic.

Excellent Design Quality

- Adopts an all-metal enclosure design for stability and durability.
- Fan-less heat dissipation design for quiet operation, noise reduction, and green energy efficiency.

Plug - and - Play

- Plug-and-play: no need to access the management interface, making installation simple and easy to use.
- Supports one-click switching among three working modes: standard switching, port isolation, and long-distance power supply, adapting to diverse scenario requirements.

Product Specifications

Attribute	ES100-10G-HP
Dimensions	186mm × 150mm × 43mm
Weight	1.06kg
Ports	10 10/100/1000Base-T electrical ports (2 uplink ports, 8 PoE+ power supply ports; maximum PoE power per port: 30W)
Button Switch - Mode Switching	Standard mode; Port isolation; Long-distance power supply
Switching Capacity	20Gbps
Packet Forwarding Rate	14.9Mpps
MAC Address Table Entries	2K
Port Lightning Protection	6kV
Total PoE Power	120W

Power Specification	90V~264V AC
Operating Temperature/Storage Temperature	0°C~40°C / -40°C~70°C
Operating Humidity/Storage Humidity	10%~90% RH / 5%~90% RH (non-condensing)
Fan	No fan, natural cooling
Certification	CE, RoHS
MTBF	> 100000H
Installation Method	Desktop
Warranty	3 years

Ordering Information

Model	Description
H3C Aolynk ES100-10G-HP	H3C Aolynk ES100-10G-HP full-gigabit PoE Ethernet switch. Supports 10 10/100/1000 BASE-T electrical ports, AC power supply.



**New H3C Technologies Co.,
Limited**

Beijing Headquarters
Tower 1, LSH Center, 8 Guangshun South
Street, Chaoyang
District, Beijing, China

Hangzhou Headquarters
466 Changhe Road, Binjiang District,
Hangzhou City
310052, China

<http://www.h3c.com>

Customer service hotline

https://www.h3c.com/en/Support/Online_Help/Service_Hotlines/

Copyright © New H3C Technologies Co., Ltd. All Rights Reserved.

Disclaimer: Although H3C has attempted to provide accurate information in this material, it does not warrant that the content of the material is free from technical errors or typographical errors, for which H3C assumes no responsibility for inaccuracies in this material.

H3C reserves the right to modify the content of this material without notice or prompt.