

HPE Networking Instant On Secure Gateways

Improve your network security and expand your business



The HPE Networking Instant On Secure Gateways are cloud-managed gateways designed for small and growing businesses looking to enhance the security of their network or safely expand to new locations. These gateways, purpose-built for SMBs, provide 24x7 network monitoring, an IDS/IPS engine, and domain blocking for enhanced protection. Thanks to hardware acceleration, with all these features active, the gateway can still provide near-line rate throughput.

Protecting SMBs from growing cyber threats

Cyber threats continue to target SMBs worldwide, primarily through ransomware and phishing scams. These attacks take advantage of vulnerable networks, hoping that users won't notice or double-check anything suspicious. HPE Networking Instant On Secure Gateways provide robust protection by monitoring all network traffic to prevent harmful files from infiltrating your network environment. The gateways also enable site-to-site communication between Instant On secured sites over VPN, ensuring connections between locations remain protected from cybercriminals.

Network Policy Assistant

The AI-powered Network Policy Assistant streamlines firewall policy creation. Just enter a prompt like "block traffic from website.com" and approve the generated

policy. Easily configure port forwarding, domain blocking, wireless scheduling, and more.

Enhanced security with the HPE Networking Instant On Secure Gateway SG1004

The HPE Networking Instant On Secure Gateway SG1004 is a 1G secure gateway featuring one uplink (WAN) port, two downlink (LAN) ports, and one configurable uplink/ downlink port. With a stateful firewall throughput of 930 Mbps, it's ideal for protecting businesses with less than one Gigabit total throughput from their ISP. The compact design and external power supply make it perfect for branch offices or small businesses like accounting firms or retail shops.



Advanced performance with the HPE Networking Instant On Secure Gateway SG2505P

For larger environments, the HPE Networking Instant On Secure Gateway SG2505P offers five ports, two of them providing multigigabit support. One multi-gig uplink (WAN) port, one multi-gig configurable port (WAN/LAN), one gig configurable port (WAN/LAN), and two one-gig ports (LAN). The 2505P has PoE support with a total power budget of 64W to power network devices such as Instant On access points. With a stateful firewall throughput of 2.3 Gbps, this gateway is ideal for businesses requiring over 1 Gigabit of total throughput from their ISP. Whether you're a small shop looking to keep the network simple or an AI startup needing to protect your large data workloads, the SG2505P will help you stay connected and more secure.

Powerful security and performance for SMBs

The HPE Networking Instant On Secure Gateways deliver a wide range of advanced technical features designed to boost network performance and enhance security for SMBs. One key feature is VPN, which provides encrypted site-to-site communication between Instant On Secure Gateway sites, allowing businesses to connect multiple locations more securely. Additionally, the built-in Intrusion Detection and Prevention System (IDS/IPS) actively monitors network traffic for suspicious activity and automatically blocks malicious content threats, ensuring the integrity of business data.

And with automatic firmware updates that keep security patches up to date and easy-to-use management through the Instant On cloud portal and mobile app, maintaining a more secure network has never been easier. The gateway also supports WAN resiliency through failover features, ensuring continuous network service even during ISP outage events.



HPE Networking Instant On Secure Gateway features

- **AI-powered Network Policy Assistant** — The integrated AI assistant in the Instant On Cloud portal can help with creating policies, creating schedules and deploying firewall rules. Let the assistant know what you are trying to do and it will create a policy to help.
- **Firewall** — monitors and filters incoming and outgoing traffic based on predefined security rules. The firewall also prevents sessions from reaching the LAN when they originate from the WAN, unless a remote access policy is enabled.
- **IDS/IPS** — IDS (Intrusion Detection System) and IPS (Intrusion Prevention System) are technologies used to monitor network traffic for suspicious activity and potential threats.
- **IDS** — detects and alerts administrators about possible security breaches or malicious activity within a network. IDS analyzes traffic for known attack patterns or anomalies; it does not actively block or prevent attacks.
- **IPS** — detects malicious activity and actively blocks or prevents those threats in real time. It can take automatic action to stop attacks, such as blocking IP addresses or terminating harmful connections.
- **IDS/IPS event logging** — malicious activities detected or blocked will be displayed in the Threats module of the Instant On app and web portal.
- **TPM 2.0 support** — a more robust, flexible, and secure version of Trusted Platform Management, TPM 2.0 is designed to meet the needs of modern and future networking needs with an advanced level of security assurance.
- **Wired and wireless application visibility** — see details of web applications accessed by clients, both wired and wireless, within the Instant On mobile app or web portal.
- **Site-to-site VPN** — connect sites together over a secure VPN when both have an Instant On Secure Gateway connected to the WAN.
- **Client VPN** — helps providing employee access to network resources remotely and securely, improving productivity and enhancing on-premises resource efficiency. Integration of WiredGuard remote access VPN helps SMBs quickly stand up remote workers right from the Instant On Cloud Portal.
- **WAN failover** — provides a backup/failover mechanism to keep the network alive by falling over to a secondary source when the network's connectivity with the primary source is down.
- **WAN load balancing** — with two active WAN links, gateways can distribute network traffic across both links simultaneously to optimize performance, increase bandwidth utilization, and provide redundancy. This ensures efficient traffic flow and enhances reliability by preventing overloading of a single link.
- **PoE support (SG2505P exclusive)** — total 64W PoE budget, power two 30W 802.3at devices such as VoIP phones, wireless access points, and security cameras, as well as any 15.4W 802.3af-compliant end devices, can be powered on by any of the four downlink ports with full POE support, mitigating the cost of additional electrical cabling and circuits that would otherwise be necessary for IP phone and WLAN deployments.
- **Locator LED** — allows admin users to have the LEDs on the gateway blink, simplifying troubleshooting by making it easy to locate a particular device within a rack.
- **Quiet LED mode** — allows users to shut off gateway LEDs for deployments when the gateway needs to be hidden.
- **VLAN support** — offers some of the benefits of both bridging and routing. VLANs partition the network into logical segments, which provides better administration, security, and multicast traffic management.



Technical specifications



HPE Networking Instant On Secure Gateway SG1004 (SOG33A)



HPE Networking Instant On Secure Gateway SG2505P (SOG34A)

| | | |
|---------------------------------|---|---|
| Processor speed | 2.0 GHz | 2.0 GHz |
| Memory | 2GB | 4GB |
| Storage (Flash) | 4GB eMMC | 4GB eMMC |
| Physical characteristics | | |
| WAN interface | 1x 10/100/1000-Base-T Ethernet | 1x 100/1000/2500-Base-T Ethernet |
| WAN/LAN configurable interface | 1x 10/100/1000-Base-T Ethernet | 1x 100/1000/2500-Base-T Ethernet 1x 10/100/1000-Base-T Ethernet |
| LAN Interfaces | 2x 10/100/1000-Base-T Ethernet | 2x 10/100/1000-Base-T Ethernet |
| Additional interfaces | – | 1 USB-A 2.0 |
| POE options | – | 4 ports PoE Cl4 |
| Dimensions (L x W x H) | 1.73 x 6.46 x 7.48in (4.39 x 16.41 x 19.00cm) | 1.73 x 12.19 x 9.22in (4.39 x 30.96 x 23.42cm) |
| Weight lb (kg) | 2.27lbs (1.03kg) | 5.29lbs (2.40kg) |
| Mounting options | Tabletop and wall | Tabletop, wall, telco rack |
| Performance | | |
| Firewall performance* | 980 Mbps | 2.4 Gbps |
| Routing performance** | 980 Mbps | 2.4 Gbps |
| IDS/IPS performance*** | 980 Mbps | 2.4 Gbps |
| VPN performance (IPSec)**** | 930 Mbps | 2.3 Gbps |
| Max concurrent client VPN users | 10 | 25 |
| Client VPN Performance | 250Mbps | 250Mbps |
| Max accelerated TCP sessions | 32K | 32K |
| Max VLAN | 22 | 22 |
| No of users | up to 100 | up to 300 |

*Packet size: 1518. Bi-directional traffic. 500 firewall rules. Test run for 30 min.

**Packet size: 1518. Bi-directional traffic. 500 firewall rules + 10 routes. Test run for 30 min.

***Packet size: 1518. Bi-directional traffic. 500 firewall rules + 10 routes + IDPS enabled. Test run for 30 min.

****Instant On Secure Gateway to Instant On Secure Gateway, UDP, packet size 1390.



Technical specifications

HPE Networking Instant On Secure Gateway SG1004 (S0G33A)

HPE Networking Instant On Secure Gateway SG2505P (S0G34A)

| Electrical characteristics | | |
|---|--|--|
| Frequency | 50/60 Hz | 50/60 Hz |
| AC voltage | 100-240 VAC | 100-127 / 200-240 VAC |
| Current | 0.3A (12VDC - 1A) | 0.8 A |
| Maximum power rating | 12W | 79.5 W |
| Idle power | 2.3 W | 5.6 W |
| PoE power | None | 64 W Class 4 PoE |
| Power supply | External power adapter (included) | Internal power supply |
| Operating temperature | 0-40C | 0-40C |
| Operating humidity | 15-95% | 15-95% |
| No. of users | up to 100 | up to 300 |
| Regulatory | | |
| Regulatory model number | RSVLC-2304 | RSVLC-2305 |
| Safety | Europe: EN 62368-1:2014 +A11:2017 EN 62368-1:2020 +A11:2020 US: UL 62368-1, 3rd Ed., Canada: CAN/CSA C22.2 No. 62368-1:19, 3rd Ed. Worldwide: IEC 62368-1:2014, 2nd Ed. IEC 62368-1: 2018, 3rd Ed. Taiwan: CNS-15598-1:2020 China: GB 4943.1:2022 | Europe: EN 62368-1:2014 +A11:2017 EN 62368-1:2020 +A11:2020 US: UL 62368-1, 3rd Ed., Canada: CAN/CSA C22.2 No. 62368-1:19, 3rd Ed. Worldwide: IEC 62368-1:2014, 2nd Ed. IEC 62368-1: 2018, 3rd Ed. Taiwan: CNS-15598-1:2020 China: GB 4943.1:2022 |
| IPsec details | | |
| Category | Specification | |
| VPN Technology | IPsec site-to-site VPN | |
| IKE Version | IKEv2 | |
| Primary Symmetric Encryption | AES-256-CBC | |
| Primary Key Exchange | Diffie-Hellman Group 32 (Curve448) | |
| Integrity Algorithms | SHA-256-HMAC | |
| Additional Symmetric Encryption | AES-128-GCM, AES-128-CBC | |
| Additional Key Exchange | Diffie-Hellman Group 31 (Curve25519), Group 21 (521 bit Random ECP) | |
| Encryption Activation | Enabled by default; no license key or PIN required | |
| Emissions | | |
| Europe: EN 55032:2015 + A11:2020, Class B EN 61000-3-2:2019 EN 61000-3-3:2013 | Europe: EN 55032:2015 + A11:2020, Class B EN 61000-3-2:2019 EN 61000-3-3:2013 | |
| US: FCC 47 CFR part 15B: 2021, Class B | US: FCC 47 CFR part 15B: 2021, Class B | |
| Canada: ICES-003 Issue 7: 2020, Class B | Canada: ICES-003 Issue 7: 2020, Class B | |
| Worldwide: VCCI-CISPR 32, Class B CISPR 32: 2016, Class B AS/NZS CISPR 32: 2015, Class B CNS 15936: 2020, Class B | Worldwide: VCCI-CISPR 32, Class B CISPR 32: 2016, Class B AS/NZS CISPR 32: 2015, Class B CNS 15936: 2020, Class B | |



Technical specifications

| | HPE Networking Instant On Secure Gateway SG1004 (SOG33A) | HPE Networking Instant On Secure Gateway SG2505P (SOG34A) |
|--------------------------------|--|---|
| Immunity | | |
| Generic certifications | CISPER 35: 2016 | CISPER 35: 2016 |
| EN | EN 55035:2017/A11:2020 | EN 55035:2017/A11:2020 |
| ESD | IEC 61000-4-2 | IEC 61000-4-2 |
| Radiated | IEC 61000-4-3 | IEC 61000-4-3 |
| EFT/Burst | IEC 61000-4-4 | IEC 61000-4-4 |
| Surge | IEC 61000-4-5 | IEC 61000-4-5 |
| Conducted | IEC 61000-4-6 | IEC 61000-4-6 |
| Power frequency magnetic field | IEC 61000-4-8 | IEC 61000-4-8 |
| Voltage dips & interruptions | IEC 61000-4-11 | IEC 61000-4-11 |
| Harmonic | IEC/EN 61000-3-2 | IEC/EN 61000-3-2 |
| Flicker | IEC/EN 61000-3-3 | IEC/EN 61000-3-3 |
| RoHS | IEC/EN 63000:2018 | IEC/EN 63000:2018 |

Ordering information

HPE Networking Instant On Secure Gateways

| Part number | Description | Comments |
|-------------|---|--|
| SOG33A | HPE Networking Instant On Secure Gateway 4-port Gigabit SG1004 | Contents will include power adapter, mounting hardware, and quick card Add # options to choose the right power cord/adaptor for the specific country |
| SOG34A | HPE Networking Instant On Secure Gateway 5-Port SmartRate 2.5G PoE+ 64W SG2505P | Contents will include region-specific power cord, mounting hardware, and quick card Add # options to choose the right power cord/adaptor for the specific country |

Support SKUs

HPE Networking Instant On Secure Gateways

| Part number | Description | Comments |
|-------------|---|--------------------------------------|
| H07BHE | HPE ANW FC 3Y NBD Exch SG1004 IONGtwySVC | 3 year Advanced Exchange for SG1004 |
| H07BJE | HPE ANW FC 3Y NBD Exch SG2505P IONGtwySVC | 3 year Advanced Exchange for SG2505P |



© Copyright 2026 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

All third-party marks are property of their respective owners.

DS_HPE-NIO_Secure-Gateways_NR_032026 A50011189ENW