Balance 20

Most Affordable SD-WAN Router
with a Proven Track Record.

At a Glance

2x

Ethernet WAN
(Gigabit Ethernet)

4x

Ethernet LAN
(Gigabit Ethernet)

1x

USB WAN Port

150Mbps

Stateful Firewall
Throughput

60Mbps

PepVPN Throughput
(No Encryption)

Up to 5

VPN Peers

Balance 20
Specifications

USB WAN Port

4x 10/100/1000M Ethernet LAN

2x 10/100/1000M Ethernet WAN

12V DC Connector

WAN Interface	2 (GE) 1x USB Interface	**Remote User Access**	Yes
LAN Interface	4 (GE)	**L2TP / PPTP VPN Server**	Yes
Stateful Firewall Throughput	150 Mbps	**Bandwidth Usage Monitor**	Yes
PepVPN Throughput (No Encryption)	60 Mbps	**QoS for VoIP and E-commerce**	Yes
PepVPN Throughput (256-bit AES)	30 Mbps	**User Groups Bandwidth Control**	Yes
Recommended Users	1 - 60	**Web Blocking**	Yes
Number of PepVPN SpeedFusion Peers	2/5[i]	**Operating Temperature**	-40° – 149° F / -40° – 65° C
Maximum Number of AP Supported	10	**Power Consumption**	15 W
Central Management	InControl 2	**Dimensions (W x D x H)**	10.2 x 5.24 x 1.38 inches / 26 x 13.3 x 3.5 cm
Drop-in Mode	Yes	**Weight**	2.2 pounds / 1 kg
Manage Pepwave AP	Yes	**Certifications**	FCC, CE, RoHS
		Warranty	1-Year Limited Warranty
		Package Content	1x Balance 20 12V2A Power Supply (ACW-601)

[i] 2 SpeedFusion Peers are enabled by default. 5 Peers can be activated with additional license (PVN-LC-05).

Ordering Information

Product Code	Model	Description
BPL-021	Balance 20	2x GE WAN ports and 4x GE LAN ports.

Feature Add-on

Product Code	Description
VN-LC-05	Enable up to 5 SpeedFusion peers.
ACW-721	Ear Mount Kit
ACW-722	1U Rack Ear Mount

peplink | PEPWAVE